

ROSTAING®

WWW.ROSTAING.COM

Safety in Progress

HEAT PROTECTION 400°C

USES

HANDLING OF HOT OBJECTS UP TO 400°C
HIGH CUT RESISTANCE



SANDOU

PRODUCT ADVANTAGES

FAST INTERNAL HEAT REMOVAL

PERFORMANCE

Model meets the requirements of the European Standards:

EN 420 1994 General Requirements
EN 388 1994 Protection Against Mechanical Hazards
EN 407 Protection Against Heat and/or Fire

Homologation delivered by the notified
Organization IFTH/LYON
N°0072/011/162/03/96/0189 EXT 01/03/96



PROTECTION LEVELS

MECHANICAL HAZARDS



- 2 Abrasion resistance out of four levels
- 4 Blade cut resistance out of five levels
- 4 Tear resistance out of four levels
- 1 Puncture resistance out of four levels

HEAT AND FIRE



- 4 Fire resistance out of four levels
- 4 Contact heat out of four levels
- X Convective heat out of four levels
- X Radiant heat out of four levels
- X Small splashes of molten metal out of four levels
- X Large splashes of molten metal out of four levels

DESCRIPTION & MAINTENANCE

Five-finger American cut glove, palm and thumb in 550 g/m² para-aramid loop pile
Back made of 1.1 mm split leather. Palm lined with wool fleece
Total length 39 cm, including a 19 cm-cuff
Para-aramid thread seams.
Packaging: 5 pair packet / 20 pair carton

Available sizes: 8. 9. 10. 11

Reference: SANDOU

Do not wash/ dry cleaning



ROSTAING SA
17, avenue Charles de Gaulle
01800 VILLIEU LOYES MOLLON

Tél : 04 74 46 07 15
Tél : 0033(0)4 74 46 34 55
Mail : contact@rostaing.fr

Fax : 04 74 61 34 43
Fax : 0033 (0) 4 74 61 34 43
Web : www.rostaing.com