

# MAMBA

## ALL-ROUND VISION!

Thanks to its many features – lightweight, non-slip bridge, co-injected temples, all-round vision – MAMBA provides perfect comfort for permanent wear.

NEW VERSION



MAMPSI



MAMPSF



MAMPSJ



27 g

SUPPLIED WITH

Adjustable cord  
CORDC



Non-slip bridge  
reinforced












Non-slip temples

- + UPPER PROTECTION**
- + NON-SLIP BRIDGE REINFORCED**
- + COMFORTABLE, NON-SLIP TEMPLES**
- + ALL-ROUND VISION**

**bolle**  
SAFETY

# MAMBA

## ALL-ROUND VISION!

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>MAMBA</b>	 Clear	MAMPSI	2C-1,2  1 FT C€	 EN166 FT C€	Anti-scratch/anti-fog
	 Smoke	MAMPSF	5-3,1  1 FT C€	 EN166 FT C€	Anti-scratch/anti-fog
	 Yellow	MAMPSJ	2C-1,2  1 FT C€	 EN166 FT C€	Anti-scratch/anti-fog

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:


C€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	MAMPSI	MAMPSF	MAMPSJ
Individual plastic bag	3660740005306	3660740005313	3660740005320
10 safety spectacles per inner box	3660740105303	3660740105310	3660740105327
300 safety spectacles per outer pack	3660740205300	3660740205317	3660740205324

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



09/09/2016

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY